

SimpleCut RTR

Label cutter

LABEL SMART

MAIN FEATURES

- ◆ Suitable for prototyping or small production
- ◆ Contour cutting is performed automatically
- ◆ Perfect for low-cost, on-demand, short run labels, specialty labels of any shape, and helps reduce inventory

CUTTING SAMPLES



SPECIFICATIONS

This parameter is subject to change without prior notice. The company reserves the right of final interpretation

Model Name	SG-LCP
Cutting control system	Digital servo motor
Maximum actual cutting speed	960mm/s
Maximum cutting force	750g
Minimum cutting character	About 5mm ²
Maximum applicable material	340 mm
Maximum sheet size	120mm
Maximum cutting size	280mm
Application industry	Advertising, Display, Packaging, Color printing, etc
Working noise	35Db
Mechanical resolution	0.02mm
Programmable resolution	HPGL 0.025mm
Minimum roller size	100mm
Maximum roller size	320mm
Maximum diameter of roller	250mm
Package dimensions	1200mm×800mm×750mm
Actual dimensions	1025mm×605mm×560mm
Gross/Net weight	110kg/75kg
Software and compatibility	
Connectivity	USBinterfaces
Software and compatibility	LabelStudio only, compatible for Windows7,8,10 (USB interfaces) Corel Draw/ Illustrator Plug-in, PC only (SD interfaces)
Power and working environment requirements	
Power source	100V ~ 240V 50/60 Hz
Power	150W
Operation environment	Temperature +5°C to +35 °C (Fahrenheit 41-95), Humility 30% -75% (Non-condensing)



Application: Self-adhesive sticker, label etc.

LABEL SMART



Tel: +2782 467 4694

sales@labelsmart.co.za

www.labelsmart.co.za